



**Transformateurs de contrôle fermés à usage général :
Tableaux de sélection**

GROUPE A

TENSION PRIMAIRE 600/480 575/460 550/440
TENSION SECONDAIRE 120X240 115X230 110X220 60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050ACP	0.42/0.21	2.70 [69]	6.34 [161]	3.43 [87]	1.65 [42]	4.17 [106]	.22 X .44 [5.6] X [11.1]	1.9
100	C2E0100ACP	0.83/0.42	3.09 [79]	6.06 [154]	3.70 [94]	2.05 [52]	3.46 [88]	.22 X .44 [5.6] X [11.1]	2.7
150	C2E0150ACP	1.25/0.63	3.09 [79]	6.61 [168]	3.70 [94]	2.05 [52]	4.01 [102]	.22 X .44 [5.6] X [11.1]	3.7
250	C2E0250ACP	2.08/1.04	3.88 [99]	6.61 [168]	4.21 [107]	2.52 [64]	3.90 [99]	.22 X .44 [5.6] X [11.1]	5.8
350	C2E0350ACP	2.92/1.46	3.88 [99]	7.20 [183]	4.21 [107]	2.52 [64]	4.49 [114]	.22 X .44 [5.6] X [11.1]	7.4
500	C2E0500ACP	4.17/2.08	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.5
750	C2E0750ACP	6.25/3.13	5.34 [136]	7.61 [193]	5.21 [132]	4.00 [102]	4.88 [124]	.31 X .81 [7.9] X [20.6]	16.5
1000	C2E1000ACP	8.33/4.17	5.34 [136]	8.40 [213]	5.21 [132]	4.00 [102]	5.67 [144]	.31 X .81 [7.9] X [20.6]	20.4
1500	C2E1500ACP	12.50/6.25	6.56 [167]	9.18 [233]	5.98 [152]	5.20 [132]	5.94 [151]	.31 X .81 [7.9] X [20.6]	34.4
2000	C2E2000ACP	16.67/8.33	6.56 [167]	9.18 [233]	5.98 [152]	5.20 [132]	5.94 [151]	.31 X .81 [7.9] X [20.6]	35.4
3000	C2E3000ACP	25.00/12.50	7.61 [193]	11.28 [287]	6.76 [172]	6.30 [160]	7.05 [179]	.31 X .81 [7.9] X [20.6]	58.0
5000	C2E5000ACP	41.67/20.83	9.10 [231]	15.76 [400]	8.04 [204]	7.40 [188]	8.03 [204]	.31 X .81 [7.9] X [20.6]	100.9

*Les dimensions sont exprimées en pouces [mm].

GROUPE B

TENSION PRIMAIRE 600 575 550

TENSION SECONDAIRE 24 23 22

60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050AR	2.08	2.70 [69]	5.75 [146]	3.43 [87]	1.65 [42]	3.58 [91]	.22 X .44 [5.6] X [11.1]	1.3
100	C2E0100AR	4.17	3.09 [79]	6.06 [154]	3.70 [94]	2.05 [52]	3.46 [88]	.22 X .44 [5.6] X [11.1]	2.6
150	C2E0150AR	6.25	3.09 [79]	6.45 [164]	3.70 [94]	2.05 [52]	3.85 [98]	.22 X .44 [5.6] X [11.1]	3.4
250	C2E0250AR	10.42	3.88 [99]	6.81 [173]	4.21 [107]	2.52 [64]	4.09 [104]	.22 X .44 [5.6] X [11.1]	6.0
350	C2E0350AR	14.58	3.88 [99]	7.20 [183]	4.21 [107]	2.52 [64]	4.49 [114]	.22 X .44 [5.6] X [11.1]	7.3
500	C2E0500AR	20.83	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.3

*Les dimensions sont exprimées en pouces [mm].

GROUPE C

TENSION PRIMAIRE 380/347

TENSION SECONDAIRE 120X240

50/60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050KHP	0.42/0.21	2.70 [69]	6.06 [154]	3.43 [87]	1.65 [42]	3.90 [99]	.22 X .44 [5.6] X [11.1]	1.7
100	C2E0100KHP	0.83/0.42	3.09 [79]	6.06 [154]	3.70 [94]	2.05 [52]	3.46 [88]	.22 X .44 [5.6] X [11.1]	2.7
150	C2E0150KHP	1.25/0.63	3.09 [79]	6.61 [168]	3.70 [94]	2.05 [52]	4.01 [102]	.22 X .44 [5.6] X [11.1]	3.8
250	C2E0250KHP	2.08/1.04	3.88 [99]	6.61 [168]	4.21 [107]	2.52 [64]	3.90 [99]	.22 X .44 [5.6] X [11.1]	5.7
350	C2E0350KHP	2.92/1.46	3.88 [99]	7.20 [183]	4.21 [107]	2.52 [64]	4.49 [114]	.22 X .44 [5.6] X [11.1]	7.3
500	C2E0500KHP	4.17/2.08	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.6
750	C2E0750KHP	6.25/3.13	5.34 [136]	7.61 [193]	5.21 [132]	4.00 [102]	4.88 [124]	.31 X .81 [7.9] X [20.6]	16.5
1000	C2E1000KHP	8.33/4.17	5.34 [136]	8.40 [213]	5.21 [132]	4.00 [102]	5.67 [144]	.31 X .81 [7.9] X [20.6]	20.7
1500	C2E1500KHP	12.50/6.25	6.52 [166]	8.79 [223]	5.98 [152]	5.16 [131]	5.54 [141]	.31 X .81 [7.9] X [20.6]	33.3

*Les dimensions sont exprimées en pouces [mm].

GROUPE D

TENSION PRIMAIRE 380/347

TENSION SECONDAIRE 24

50/60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions hors tout			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050KHR	2.08	2.70 [69]	6.06 [154]	3.43 [87]	1.65 [42]	3.90 [99]	.22 X .44 [5.6] X [11.1]	1.7
100	C2E0100KHR	4.17	3.09 [79]	6.26 [159]	3.70 [94]	2.05 [52]	3.66 [93]	.22 X .44 [5.6] X [11.1]	2.9
150	C2E0150KHR	6.25	3.09 [79]	6.61 [168]	3.70 [94]	2.05 [52]	4.01 [102]	.22 X .44 [5.6] X [11.1]	3.8
250	C2E0250KHR	10.42	3.88 [99]	6.61 [168]	4.21 [107]	2.52 [64]	3.90 [99]	.22 X .44 [5.6] X [11.1]	5.8
350	C2E0350KHR	14.58	3.88 [99]	7.40 [188]	4.21 [107]	2.52 [64]	4.69 [119]	.22 X .44 [5.6] X [11.1]	7.8
500	C2E0500KHR	20.83	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.3

*Les dimensions sont exprimées en pouces [mm].

GROUPE E

TENSION PRIMAIRE 240X480 230X460 220X440

TENSION SECONDAIRE 120X240 115X230 110X220

50/60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050MQMJ	0.42/0.21	2.70 [69]	5.87 [149]	3.43 [87]	1.65 [42]	3.70 [94]	.22 X .44 [5.6] X [11.1]	1.5
100	C2E0100MQMJ	0.83/0.42	3.09 [79]	6.06 [154]	3.70 [94]	2.05 [52]	3.46 [88]	.22 X .44 [5.6] X [11.1]	2.6
150	C2E0150MQMJ	1.25/0.63	3.09 [79]	6.61 [168]	3.70 [94]	2.05 [52]	4.01 [102]	.22 X .44 [5.6] X [11.1]	3.8
250	C2E0250MQMJ	2.08/1.04	3.88 [99]	6.61 [168]	4.21 [107]	2.52 [64]	3.90 [99]	.22 X .44 [5.6] X [11.1]	5.7
350	C2E0350MQMJ	2.92/1.46	3.88 [99]	7.20 [183]	4.21 [107]	2.52 [64]	4.49 [114]	.22 X .44 [5.6] X [11.1]	7.2
500	C2E0500MQMJ	4.17/2.08	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.6
750	C2E0750MQMJ	6.25/3.13	5.34 [136]	7.61 [193]	5.21 [132]	4.00 [102]	4.88 [124]	.31 X .81 [7.9] X [20.6]	17.0
1000	C2E1000MQMJ	8.33/4.17	5.34 [136]	8.40 [213]	5.21 [132]	4.00 [102]	5.67 [144]	.31 X .81 [7.9] X [20.6]	21.2
1500	C2E1500MQMJ	12.50/6.25	6.56 [167]	9.18 [233]	5.98 [152]	5.20 [132]	5.94 [151]	.31 X .81 [7.9] X [20.6]	35.6
2000	C2E2000MQMJ	16.67/8.33	6.60 [168]	9.57 [243]	5.98 [152]	5.24 [133]	6.33 [161]	.31 X .81 [7.9] X [20.6]	39.0
3000	C2E3000MQMJ	25.00/12.50	7.61 [193]	11.28 [287]	6.76 [172]	6.30 [160]	7.05 [179]	.31 X .81 [7.9] X [20.6]	58.8
5000	C2E5000MQMJ	41.67/20.83	9.10 [231]	15.76 [400]	8.04 [204]	7.40 [188]	8.03 [204]	.31 X .81 [7.9] X [20.6]	104.6

*Les dimensions sont exprimées en pouces [mm].

GROUPE F

TENSION PRIMAIRE 277

TENSION SECONDAIRE 120

50/60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050NJ	0.42	2.70 [69]	6.06 [154]	3.43 [87]	1.65 [42]	3.90 [99]	.22 X .44 [5.6] X [11.1]	1.7
100	C2E0100NJ	0.83	3.09 [79]	6.06 [154]	3.70 [94]	2.05 [52]	3.46 [88]	.22 X .44 [5.6] X [11.1]	2.7
150	C2E0150NJ	1.25	3.09 [79]	6.61 [168]	3.70 [94]	2.05 [52]	4.01 [102]	.22 X .44 [5.6] X [11.1]	3.7
250	C2E0250NJ	2.08	3.88 [99]	6.61 [168]	4.21 [107]	2.52 [64]	3.90 [99]	.22 X .44 [5.6] X [11.1]	5.7
350	C2E0350NJ	2.92	3.88 [99]	7.20 [183]	4.21 [107]	2.52 [64]	4.49 [114]	.22 X .44 [5.6] X [11.1]	7.4
500	C2E0500NJ	4.17	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.5
750	C2E0750NJ	6.25	5.34 [136]	7.61 [193]	5.21 [132]	4.00 [102]	4.88 [124]	.31 X .81 [7.9] X [20.6]	16.4
1000	C2E1000NJ	8.33	5.34 [136]	8.40 [213]	5.21 [132]	4.00 [102]	5.67 [144]	.31 X .81 [7.9] X [20.6]	21.1
1500	C2E1500NJ	12.50	5.34 [136]	9.39 [238]	5.21 [132]	4.00 [102]	6.65 [169]	.31 X .81 [7.9] X [20.6]	25.9

*Les dimensions sont exprimées en pouces [mm].

GROUPE G

TENSION PRIMAIRE 120X240

TENSION SECONDAIRE 24

50/60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050PR	2.08	2.70 [69]	6.06 [154]	3.43 [87]	1.65 [42]	3.90 [99]	.22 X .44 [5.6] X [11.1]	1.7
100	C2E0100PR	4.17	3.09 [79]	6.06 [154]	3.70 [94]	2.05 [52]	3.46 [88]	.22 X .44 [5.6] X [11.1]	2.7
150	C2E0150PR	6.25	3.09 [79]	6.61 [168]	3.70 [94]	2.05 [52]	4.01 [102]	.22 X .44 [5.6] X [11.1]	3.8
250	C2E0250PR	10.42	3.88 [99]	6.61 [168]	4.21 [107]	2.52 [64]	3.90 [99]	.22 X .44 [5.6] X [11.1]	5.8
350	C2E0350PR	14.58	4.59 [117]	6.83 [173]	4.70 [119]	3.25 [83]	4.09 [104]	.31 X .81 [7.9] X [20.6]	8.8
500	C2E0500PR	20.83	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.6

*Les dimensions sont exprimées en pouces [mm].

GROUPE H

TENSION PRIMAIRE 240X480

TENSION SECONDAIRE 24

50/60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050QR	2.08	2.70 [69]	6.06 [154]	3.43 [87]	1.65 [42]	3.90 [99]	.22 X .44 [5.6] X [11.1]	1.7
100	C2E0100QR	4.17	3.09 [79]	6.26 [159]	3.70 [94]	2.05 [52]	3.66 [93]	.22 X .44 [5.6] X [11.1]	2.9
150	C2E0150QR	6.25	3.09 [79]	6.61 [168]	3.70 [94]	2.05 [52]	4.01 [102]	.22 X .44 [5.6] X [11.1]	3.8
250	C2E0250QR	10.42	3.88 [99]	6.81 [173]	4.21 [107]	2.52 [64]	4.09 [104]	.22 X .44 [5.6] X [11.1]	6.2
350	C2E0350QR	14.58	3.88 [99]	7.40 [188]	4.21 [107]	2.52 [64]	4.69 [119]	.22 X .44 [5.6] X [11.1]	7.8
500	C2E0500QR	20.83	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.6

*Les dimensions sont exprimées en pouces [mm].

GROUPE I
 TENSION PRIMAIRE 208X416 199X398 190X380
 TENSION SECONDAIRE 120X240 115X230 110X220 50/60 Hz

VA	Numéro de catalogue	Courant de sortie	Dimensions			Centres de montage		Fente de montage	Pds. approx. de transport (lbs)
			A	B	C	D	E	G X H	
50	C2E0050SP	0.42/0.21	2.70 [69]	5.87 [149]	3.43 [87]	1.65 [42]	3.70 [94]	.22 X .44 [5.6] X [11.1]	1.5
100	C2E0100SP	0.83/0.42	3.09 [79]	6.26 [159]	3.70 [94]	2.05 [52]	3.66 [93]	.22 X .44 [5.6] X [11.1]	3.0
150	C2E0150SP	1.25/0.63	3.88 [99]	6.10 [155]	4.21 [107]	2.52 [64]	3.39 [86]	.22 X .44 [5.6] X [11.1]	4.1
250	C2E0250SP	2.08/1.04	3.88 [99]	6.81 [173]	4.21 [107]	2.52 [64]	4.09 [104]	.22 X .44 [5.6] X [11.1]	6.2
350	C2E0350SP	2.92/1.46	4.59 [117]	6.83 [173]	4.70 [119]	3.25 [83]	4.09 [104]	.31 X .81 [7.9] X [20.6]	8.8
500	C2E0500SP	4.17/2.08	4.59 [117]	7.22 [183]	4.70 [119]	3.25 [83]	4.49 [114]	.31 X .81 [7.9] X [20.6]	10.8
750	C2E0750SP	6.25/3.13	5.34 [136]	7.61 [193]	5.21 [132]	4.00 [102]	4.88 [124]	.31 X .81 [7.9] X [20.6]	16.7
1000	C2E1000SP	8.33/4.17	5.34 [136]	8.40 [213]	5.21 [132]	4.00 [102]	5.67 [144]	.31 X .81 [7.9] X [20.6]	21.4
1500	C2E1500SP	12.50/6.25	6.56 [167]	9.18 [233]	5.98 [152]	5.20 [132]	5.94 [151]	.31 X .81 [7.9] X [20.6]	36.0

*Les dimensions sont exprimées en pouces [mm].



