

# PRODUCT DATA SHEET

Open Style Control Transformer

Cat. Number: C2G1500SP

Rating: 1.5KVA  
 Phase: 1  
 Freq: 50/60 Hz  
 Temp. Rise: 80°C  
 Enclosure: Core & Coil  
 Material: Copper  
 Ins. Class: 130°C

| DIMENSIONS |     |       |
|------------|-----|-------|
|            | in  | mm    |
| Height     | 5.7 | 144.8 |
| Width      | 6.4 | 161.9 |
| Depth      | 7.2 | 184.1 |

|        | lbs  | kg   |
|--------|------|------|
| Weight | 35.1 | 15.9 |

| PRIMARY     |                          | SECONDARY   |                          |
|-------------|--------------------------|-------------|--------------------------|
| Voltage     | 208X416                  | Voltage     | 120X240                  |
| Connection  | Parallel x Series (Vx2V) | Connection  | Parallel x Series (Vx2V) |
| Termination | Terminal Block           | Termination | Terminal Block           |

|                                    |                             |
|------------------------------------|-----------------------------|
| Load Inrush VA at 40% Power Factor | 5% Voltage Drop @ 5655 VA   |
|                                    | 10% Voltage Drop @ 9790 VA  |
|                                    | 15% Voltage Drop @ 13755 VA |
| Full Load Watts Loss               | 90.3 Watts                  |

|                   |                         |
|-------------------|-------------------------|
| Country of Origin | Mexico                  |
| Certifications    | CSA: LR3902, UL: E50394 |