



HPS PowerPlus™

Mini Power Centers

power to perform



Hammond
Power Solutions

HPS PowerPlus™

Mini Power Centers


HPS PowerPlus™ is a convenient pre-wired power center that saves you time, money, and space. HPS PowerPlus™ combines a pre-wired primary and secondary breaker, secondary power panel, and dry-type shielded transformer in a Type 3R enclosure. Simply add the required branch circuit breakers and you effortlessly have a power center that is ready for indoor or outdoor use!

FEATURES

- Type 3R indoor/outdoor enclosure (optional 316 Stainless Steel enclosure available)
- 480 Primary, 120/240 Secondary
- Shielded transformer
- 180° insulation class
- 115° temperature rise
- Primary taps: 2 - 5% FCBN
- Meet NEMA, ANSI, & OSHA standards
- 15 year limited warranty on transformer
- 1 year limited warranty on Mini Power Center

APPLICATIONS

- Industrial locations
- Temporary power at construction sites
- Commercial buildings
- Test equipment
- Plant assembly lines




Transformer: HPS shielded transformers are encapsulated for general purpose indoor or outdoor use within a variety of environments. An electrostatic shield is placed between the primary and secondary winding and grounded to reduce electrical interference and to provide additional protection.

Panel Assembly: The HPS PowerPlus™ assembly comes fully equipped with a primary & secondary main circuit breaker. It will hold up to 20 1-pole or 10 2-pole, one inch, common trip, duplex secondary branch circuit breakers (snap-in) and ground fault circuit breakers. Once you have established your branch circuit requirements, contact your local distributor to obtain your branch circuit breakers.

Connections: HPS PowerPlus™ accepts Aluminum or Copper conductor.

Protection: The transformer is protected by the primary main breaker, which handles high interrupting fault conditions. The N.E.C. requires a secondary breaker to be between the transformer and the panel.

Approvals: HPS PowerPlus™: 

SINGLE PHASE ALUMINUM SPECIFICATIONS

480 Primary 120/240 Secondary  60 Hz

kVA Rating	Catalog Number	Max. Secondary Circuits*		Overall Dimensions			Weight Lbs.
		120 V (1 Pole)	240 V (2 Pole)	Width	Depth	Height	
Type 3R Enclosure							
5	M1PC005LESF	8	4	11.250	7.750	31.938	127
7.5	M1PC007LESF	8	4	13.875	11.125	31.938	201
10	M1PC010LESF	8	4	13.875	11.125	34.188	210
15	M1PC015LESF	12	6	15.125	12.500	34.188	291
25	M1PC025LESF	20	10	16.250	13.625	41.563	423
316 Stainless Steel Enclosure							
5	M1PC005LESF7	8	4	11.250	7.750	31.938	127
7.5	M1PC007LESF7	8	4	13.875	11.125	31.938	201
10	M1PC010LESF7	8	4	13.875	11.125	34.188	210
15	M1PC015LESF7	12	6	15.125	12.500	34.188	291
25	M1PC025LESF7	20	10	16.250	13.625	41.563	423

*Please contact factory for exact number of secondary circuits available.


Circuit Breaker Part Numbers

kVA	Primary Breaker	Secondary Breaker	Max. Rating Secondary Breaker
5	ED42B020	Q225	25
7.5	ED42B025	Q235	35
10	ED42B035	Q250	50
15	ED42B050	Q270	70
25	ED42B090	Q2110	110


Secondary: 10,000 Amps RMS Symmetrical Interrupting Capacity.
 Primary: 18,000 Amps RMS Symmetrical Interrupting Capacity @ 480V. Circuit Breakers listed above are Siemens part numbers.
Breakers can be purchased from your local HPS Distributor.




HPS PowerPlus™ is your compact economical solution!




5 kVA




7.5 kVA



10 kVA



15 kVA



25 kVA



CANADA



UNITED STATES



INDIA

CANADA

Hammond Power Solutions
595 Southgate Drive
Guelph, Ontario N1G 3W6
Tel: (519) 822-2441
Fax: (519) 822-9701
Toll Free: 1-888-798-8882
sales@hammondpowersolutions.com

UNITED STATES

Hammond Power Solutions
1100 Lake Street
Baraboo, Wisconsin 53913-2866
Tel: (608) 356-3921
Fax: (608) 355-7623
Toll Free: 1-866-705-4684
sales@hammondpowersolutions.com

INDIA

Hammond Power Solutions Pvt. Ltd.
D. No. 5-2/222/IP/B, II-Floor, Icon Plaza
Allwyn X-Roads, Miyapur, Hyderabad 500 049
Tel: +91-994-995-0009
marketing-india@hammondpowersolutions.com

EUROPE (Sales Office)

Hammond Power Solutions SpA
Tel: +49 (152) 08800468
sales@hpseurope.eu



Distributed by:

